



NON-CONDENSING ULTRA-LOW NOX

- Category III stainless steel venting
- Complies with Ultra-Low Nox regulations
- Indoor models have integrated controls and diagnostics
- Outdoor models include remote control as a standard feature
- Gas convertible from natural gas to propane using supplied kit
- 15-year limited residential heat exchanger warranty
- 5-year limited commercial heat exchanger warranty
- 5-year limited parts warranty

Model Number*	Type	BTU/h Input Natural/Propane		UEF
		Minimum	Maximum	
GTS-110U-NI	Indoor	15,000	140,000	0.81
GTS-310U-NI	Indoor	15,000	190,000	0.81
GTS-510U-NI	Indoor	15,000	199,000	0.81
GTS-110U-NE	Outdoor	15,000	140,000	0.81
GTS-310U-NE	Outdoor	15,000	190,000	0.81
GTS-510U-NE	Outdoor	15,000	199,900	0.81

Model Number*	Hot Water Output (GPM)			Unit Weight (lbs.)
	Max.	45°F Rise	70°F Rise	
GTS-110U-NI	6.6	5.1	3.3	37
GTS-310U-NI	8.0	6.9	4.4	37
GTS-510U-NI	10.0	7.2	4.7	39
GTS-110U-NE	6.6	5.1	3.3	37
GTS-310U-NE	8.0	6.9	4.4	37
GTS-510U-NE	10.0	7.2	4.7	39

*Units are field convertible from natural gas to propane with supplied conversion kit.



THE SMARTER WAY TO HEAT WATER

State tankless water heaters are designed to give you continuous* hot water while helping you save money. Heating water only when you're using it, State models incur no standby energy losses, providing efficient heating while conserving energy. They also provide great peak-time flexibility for households with multiple members—no more worries about staggering showers or delaying laundry.

State tankless water heaters take up much less space than conventional tank-type water heaters or boilers, utilizing a wall mount design that allows for additional storage and flexibility. With durable, commercial-grade parts, State water heaters are built to deliver reliable performance year after year.

*When sized appropriately for your home's needs.



TANKLESS

RESIDENTIAL GAS WATER HEATERS



statewaterheaters.com | 800.527.1953

500 Tennessee Waltz Parkway | Ashland City, TN 37015

SBGBR0311 | © March 2022 State Industries, LLC | Printed in U.S.A.

SOLID. STATE.



CONDENSING WITH X3[®] SCALE PREVENTION TECHNOLOGY

- No annual descaling required
- No hardwater exclusions in the industry's first "peace of mind" limited warranty
- No scale buildup means the heater maintains like-new performance longer
- 3" venting up to 70 equivalent feet
- ENERGY STAR[®] qualified
- 15-year limited residential heat exchanger warranty
- 1-year limited commercial heat exchanger warranty
- 5-year limited parts warranty

Model Number*	Type	BTU/h Input Natural/Propane		UEF
		Minimum +	Maximum	
GTS-240X3-NIH	Indoor	15,000	160,000	0.94
GTS-340X3-NIH	Indoor	15,000	180,000	0.95
GTS-540X3-NIH	Indoor	15,000	199,000	0.93
GTS-240X3-NEH	Outdoor	15,000	160,000	0.95
GTS-340X3-NEH	Outdoor	15,000	180,000	0.94
GTS-540X3-NEH	Outdoor	15,000	199,000	0.95

Model Number*	Hot Water Output (GPM)			Unit Weight (lbs.)
	Max.	45°F Rise	70°F Rise	
GTS-240X3-NIH	6.6	6.6	4.3	72
GTS-340X3-NIH	8.0	7.6	4.9	72
GTS-540X3-NIH	10.0	8.4	5.4	73
GTS-240X3-NEH	6.6	6.6	4.3	71
GTS-340X3-NEH	8.0	7.6	4.9	71
GTS-540X3-NEH	10.0	8.4	5.4	73

*For Propane, change the N to P in the model number when ordering:
Example: GTS-540X3-PIH
+Propane (LP) Gas Btu/h is 13,000.



HIGH EFFICIENCY CONDENSING

- Ultra-Low NOx condensing technology provides significant energy cost savings
- ENERGY STAR[®] qualified
- Indoor models have integrated controls & diagnostics
- Outdoor models include remote control as standard feature
- 15-year limited residential heat exchanger warranty
- 5-year limited commercial heat exchanger warranty
- 5-year limited parts warranty

Model Number*	Type	BTU/h Input Natural/Propane		UEF
		Minimum+	Maximum	
GTS-140-NIH	Indoor	15,000	120,000	0.90
GTS-240-NIH	Indoor	15,000	160,000	0.94
GTS-340-NIH	Indoor	15,000	180,000	0.95
GTS-540-NIH	Indoor	15,000	199,000	0.93
GTS-540P-NIH	Indoor	15,000	199,000	0.93
GTS-140-NEH	Outdoor	15,000	120,000	0.91
GTS-240-NEH	Outdoor	15,000	160,000	0.95
GTS-340-NEH	Outdoor	15,000	180,000	0.94
GTS-540-NEH	Outdoor	15,000	199,000	0.95
GTS-540P-NEH	Outdoor	15,000	199,000	0.95

Model Number*	Hot Water Output (GPM)			Unit Weight (lbs.)
	Max.	45°F Rise	70°F Rise	
GTS-140-NIH	6.6	5.0	3.2	44
GTS-240-NIH	6.6	6.6	4.3	58
GTS-340-NIH	8.0	7.6	4.9	58
GTS-540-NIH	10.0	8.4	5.4	59
GTS-540P-NIH	10.0	8.4	5.4	59
GTS-140-NEH	6.6	5.0	3.2	44
GTS-240-NEH	6.6	6.6	4.3	58
GTS-340-NEH	8.0	7.6	4.9	58
GTS-540-NEH	10.0	8.4	5.4	59
GTS-540-NEH	10.0	8.4	5.4	59
GTS-540P-NEH	10.0	8.4	5.4	59

*For Propane, change the N to P in the model number when ordering:
Example: GTS-240-PIH.
+Propane (LP) Gas minimum Btu/h is 13,000. Except GTS-140 models.



NON-CONDENSING CONCENTRIC VENT

- Complies with Ultra-Low NOx regulations
- Gas convertible from natural gas to propane using supplied kit
- Vents with contractor preferred concentric venting
- Models have integrated controls and diagnostics
- 15-Year limited residential heat exchanger warranty
- 5-Year limited commercial heat exchanger warranty
- 5-Year limited parts warranty

Model Number*	Type	BTU/h Input Natural/Propane		UEF
		Minimum	Maximum	
GTS-310C-NI	Indoor	15,000	190,000	0.81
GTS-510C-NI	Indoor	15,000	199,000	0.81

Model Number*	Hot Water Output (GPM)			Unit Weight (lbs.)
	Max.	45°F Rise	70°F Rise	
GTS-310C-NI	8.0	6.9	4.4	51
GTS-510C-NI	10.0	7.2	4.7	51

*Indoor models only. Units are field convertible from natural gas to propane with supplied conversion kit.